

SATO Safety Band UHF RFID

DT Adult Adhesive Wristband

RFID wristband for patient identification & tracking.


Specifications

PRODUCT CHARACTERISTICS	
Printing Method	Direct Thermal
Material	Anti-microbial synthetic polypropylene material
Closure Type	Adhesive closure with tamper proof system
Resistance	Water, hot water, soap, hand sanitizer, solvents
Certifications	ISO 10993-5 (Cytotoxicity), ISO 22196 (Anti-microbial), Latex free, Phthalates free
MEDIA CHARACTERISTICS	
RFID standard	EPC Class1 Gen2, ISO/IEC 18000-6
Operating frequency	UHF 860-960MHz
Chip	NXP Ucode 8
IC memory size	EPC memory: 128bits, User memory: none
Black I-mark	Yes, near edge
Packaging specifications	75 wb/roll, 16 rolls per box
Use environment	5°C to 40°C, 40% to 80%RH
Storage	0 °C to 40°C, 30% to 80%RH
PHYSICAL CHARACTERISTICS	
Item Number	162014251
Wristband size	355.6mm x 29mm
RFID inlay size	56mm x 29 mm
Printable area	124mmx29mm
Available color	White
PERFORMANCE DATA	
Read range (as reference)	Around 2m*1 up to 10m*2
Encoding times	~100,000
Data retention	Up to 50 years

Read Range (as reference)

*1 When worn at wrist, *2 When nothing in contact. Depends on device, circumstance, frequency etc.

Layout



Copyrights

The contents of this document are proprietary information of SATO Corporation and/or its subsidiaries in Japan, the U.S and other countries. No part of this document may be reproduced, copied, translated or incorporated in any other material in any form or by any means, whether manual, graphic, electronic, mechanical or otherwise, without the prior written consent of SATO Corporation.

Limitation of Liability

SATO Corporation and/or its subsidiaries in Japan, the U.S. and other countries, makes no representations or warranties of any kind regarding this material, including, but not limited to, implied warranties of merchantability and fitness for a particular purpose. SATO Corporation shall not be held responsible for errors contained herein or any omissions from the materials or for any damages, whether direct, indirect, incidental or consequential, in connection with the furnishing, distribution, performance, or use of this material.

SATO Corporation reserves the right to change or improve this product and document without notice.



satoeurope.com



SATO WS2 Printer

Recommended for printing SATO DT Wristbands

All information in this leaflet is accurate as of 2022 March.
Product specifications are subject to change without notice.
Any unauthorized reproduction of the contents of this leaflet,
in part or whole, is strictly prohibited.
All other software, product or company names are trademarks
or registered trademarks of their respective owners.

SATO
Powered **On Site** /