



MDR-1109 **Desktop Reader**

The only RFID technology you don't have to work around

MDR-1109 DESKTOP READER

The MDR-1109 is the smallest of SATO's standalone desktop PJM RFID readers. It is a very cost effective reader designed for applications where a limited number of stacked tags or a single tag will be presented to the reader for any purpose such as administrative tasks, access control or for tag issuing operations.

The compact and robust design of the MDR-1109 ensure its suitability for use in most RFID environments including Healthcare, where sensitive equipment may be present - even in operating theatres. The concise clearly defined read area ensures only the desired RFID tag is identified when presented to the reader surface eliminating any ambiguity in tag reading/issuing.

The MDR-1109 Reader is very light weight and portable and the small footprint does not consume valuable desk space, the reader can even be embedded into existing work spaces. As with all of SATO's PJM RFID readers the MDR-1109 is supplied with SATO's Reader Manager Software which provides an easy to use platform for reader setup, configuration and testing, ensuring the MDR-1109 reader is setup & ready to work with your application in virtually no time.

ELECTRICAL		<div><div>✓</div> Performs read and write operations</div> <div><div>✓</div> No manual calibration needed</div> <div><div>✓</div> Readers can be placed in close proximity to one another</div> <div><div>✓</div> RFID field unaffected by liquids</div> <div><div>✓</div> Safe to use in medical application</div>														
Operating Frequency	13.56 MHz															
ISO/IEC Compliance	18000-3 Mode 2															
Command Data Rate	424 kbit/s															
Reply Data Rate per Channel	106 kbit/s															
Number of PJM Reply Channels	2	<div>CERTIFICATIONS</div> <table><tr><td>USA (FCC)</td><td>Complies with FCC Part15 Low Power Communications Device</td></tr><tr><td>Australia</td><td>AS/NZS CISPR 22(2006), EN55022, AS/NZS 4268 (2003), AS/NZS 60950, RPS3 (ARPANSA)</td></tr><tr><td>Europe (CE Mark)</td><td>EN55022, EN 301 489-1 V1.6.1, EN 301 489-1 V2.1.1, EN 301 489-3 V1.4.1, EN 301 489-3 V1.6.1, EN 61000-3-2, EN 61000-3-3, EN 61000-4-2, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-11, EN 60950.1, EN 300 330-1 V1.3.1, EN 300 330-1 V2.1.1, EN 300 330-2 V1.3.1, EN 50364, EN 50357, RoHS</td></tr><tr><td>Thailand</td><td>NBTC</td></tr><tr><td>Singapore (IDA)</td><td>Registration Number: N0421-15</td></tr><tr><td>India</td><td>Approval Number: NR-ETA/7381-RLO(NR)</td></tr><tr><td>Japan</td><td>MIK/KS: AC-14042</td></tr></table>	USA (FCC)	Complies with FCC Part15 Low Power Communications Device	Australia	AS/NZS CISPR 22(2006), EN55022, AS/NZS 4268 (2003), AS/NZS 60950, RPS3 (ARPANSA)	Europe (CE Mark)	EN55022, EN 301 489-1 V1.6.1, EN 301 489-1 V2.1.1, EN 301 489-3 V1.4.1, EN 301 489-3 V1.6.1, EN 61000-3-2, EN 61000-3-3, EN 61000-4-2, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-11, EN 60950.1, EN 300 330-1 V1.3.1, EN 300 330-1 V2.1.1, EN 300 330-2 V1.3.1, EN 50364, EN 50357, RoHS	Thailand	NBTC	Singapore (IDA)	Registration Number: N0421-15	India	Approval Number: NR-ETA/7381-RLO(NR)	Japan	MIK/KS: AC-14042
USA (FCC)	Complies with FCC Part15 Low Power Communications Device															
Australia	AS/NZS CISPR 22(2006), EN55022, AS/NZS 4268 (2003), AS/NZS 60950, RPS3 (ARPANSA)															
Europe (CE Mark)	EN55022, EN 301 489-1 V1.6.1, EN 301 489-1 V2.1.1, EN 301 489-3 V1.4.1, EN 301 489-3 V1.6.1, EN 61000-3-2, EN 61000-3-3, EN 61000-4-2, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-11, EN 60950.1, EN 300 330-1 V1.3.1, EN 300 330-1 V2.1.1, EN 300 330-2 V1.3.1, EN 50364, EN 50357, RoHS															
Thailand	NBTC															
Singapore (IDA)	Registration Number: N0421-15															
India	Approval Number: NR-ETA/7381-RLO(NR)															
Japan	MIK/KS: AC-14042															
Number of Axis	1															
Power Supply	12VDC															
DC Power Supply Connector	2.5 mm DC centre pin positive															
Mains Input	110 - 240 VAC @ 50/60 Hz															
Mains Connector	IEC 320/C14															
Power Consumption	6W															
PERFORMANCE																
Operating Range	Marked read/write area															
Identification rate with 100% accuracy	Up to 150 tags/s															
Identify & read 96 bits of data with 100% accuracy	up to 100 tags/s															
Identify, write & read 96 bits of data with 100% accuracy	up to 50 tags/s															
HOST																
Host Interface	USB and Ethernet (Ethernet cable must be shielded (CAT 5/6))															
Host Computer	Windows 7 or later															
SOFTWARE																
Firmware Reader Server	3.48.2 or later															
ENVIRONMENT																
Operation environment	Indoor use															
Temperature Range	+10°C to +45°C															
Humidity	10% to 80% (non-condensing)															

</

